



ARROW™
LOCK & DOOR HARDWARE

N Series Deadlocks

Rainer Security Products Ltd

Unit B6, Rudford Industrial Estate, Ford, Arundel, West Sussex BN18 0BF

☎ +44 (0) 1903 732211 🌐 rainersecurity.co.uk ✉ sales@rainersecurity.co.uk



N Series Deadlock

Arrow N Series Mortice deadlock security and mortice cylinder convenience with interchangeable core compatibility.



Certification & Compliance:

- Underwriters Laboratories (UL and CUL) listed for use on A label or lesser doors when used in conjunction with a rated primary latching device

General Specifications:

Housing – Heavy wrought steel with zinc dichromate finish.

Deadbolt – 1" (25.40mm), throw solid brass deadbolt with hardened steel pin.

Backset – 2-3/4" (69.85mm).

Doors – 1-3/8" (34.92mm) to 1-3/4" (44.45mm) thick standard.

Strikes – Supplied standard with #380 security strike for steel frame and #356 security strike for wood frame.

Handing – All functions are reversible.

Cylinder Standard – Accepts 6 or 7 pin, small format, interchangeable cores. Supplied less cores. Will accept Best™ type cores.

Cylinder, Option accepts standard 1-1/8"

mortise cylinder – Solid brass, Arrow "A" keyway, drilled for 6 pins, pinned to 5. Supplied with two brass keys.

N Series Deadlock

Functions:

ARROW	ANSI	FUNCTION	DESCRIPTION/OPERATION
N40		Exit	Throw or retract bolt by thumbturn only.
N41	E06071	Single Cylinder	Throw or retract bolt by key outside, thumbturn inside.
N42	E06061	Double Cylinder	Throw or retract bolt by key either side.
N43	E06081	Single Cylinder	Throw or retract bolt by key one side.
N44	E06091	Classroom	Throw or retract bolt by key—Thumbturn retracts dead bolt, but does not project it.

Order Example:

Example: To order a N Series Single Cylinder Deadlock, Satin Chromium Plated finish with a 1-1/8" x 3-1/2" square corner strike, a 1" deadbolt, keyed different.

Specify:

Standard: **N** **41** **26D** **380** **IC**

Series Function Finish Strike Keying Cylinder

