

Rim & Threaded Cylinders



Cylinders & IC Products - Housings

Mortice Cylinder Housings: • Body–Brass, 1-5/32" diameter • Furnished–with cam, cylinder collar

- Length-1-1/8" 6 pin only; 1-1/4" 6 or 7 pin

Rim Cylinder Housing:

- Body-Brass, 1-5/32" diameter; 7 pin tumbler
- Furnished-with backplate, cylinder collar 2 screws, tailpiece

Mortice Cylinder Housing



Tapered Mortice Cylinder Housing



Rim Cylinder Housing



Rear Staked on Cam



MCF-AM2

Finish:

• Satin Chrome (26D) or Polished Brass (04) as standard

IC Housings:

Mortice Housings

Description (AR18 cam supplied unless otherwise specified)		Part No.
7	Standard	MCF-AR18
7-pin housings, 1-1/4"	Tapered	MCT-AR18


Rim Housings

Cylinders	Part No.
7-pin housing	R.C.

Cams:

Staked cams for mortise cylinder housing

CAT NO.	FUNCTIONS & APPLICATION
16CR-001	12, 17, 22, 23, 24, 27, 32 I/S, 33, 37
16CR-AM2	11, 13, 15, 16, 19, 20, 21, 31, 32 0/5, 34, 38, 41, 42, 44
16CR-004	N Series, Exit Device, Exit Alarms
16CR-006	Schlage
16CR-AR18	Adams Rite



CAT NO.	FUNCTIONS & APPLICATION
001	12, 17, 22, 23, 24, 27, 32 I/S, 33, 37
AM2	11, 13, 15, 16, 19, 20, 21, 31, 32 O/S, 34, 38, 41, 42, 44
004	N Series, Exit Device, Exit Alarms
006	Schlage
AR18	Adams Rite



16CR-001



16CR-AM2



16CR-004



16CR-006



16CR-AR18











Spacers:

CAT NO.	DESCRIPTION
16CR-123-1	1/8" Spacer - Blocking Ring
16CR-123-2	1/4" Spacer - Blocking Ring
16CR-123-3	3/8" Spacer - Blocking Ring
16-113A	Cylinder Collar & Spring

1/8" Spacer



16CR-123-2

1/4" Spacer

16CR-123-3

3/8" Spacer

Collar & Spring





